

Water Activity Meter

EZ-200



Water Activity Meter EZ-200

Features

- Reduced measurement time (30% faster than the conventional product)
- Accurately measure Aw with a sensor less susceptible to alcohol
- Easy replacement and calibration of the sensor (tools not necessary)
- Suppress sensor deterioration due to acid by placing a sensor protection filter (option)
- Device storage of up to 100 measurement data; USB memory compatible (CSV output)
- Domestic product with reliable follow-up services

Main information screens of the touch panel



Product Specifications

Product name	Water Activity Meter
Model	EZ-200
Sensor	Electrical resistance type
Measurement range	Aw 0.10-0.98 Select "Round off," "Round down," or "Round up" of the third decimal place to show value with two decimal places.
Measurement accuracy	Aw ± 0.01 (25 $\pm 0.3^\circ\text{C}$)
Measurement time	On average 10 minutes/sample
Calibration	4 points (Aw 0.33, 0.53, 0.75 and 0.93)/ 25°C
Use environment	15-35°C (no condensation)
Electricity requirements	100-240V, 47-63Hz
Dimensions	165(W) \times 130(H) \times 270(D) mm
Weight	4.3 Kg
Accessories	Power adapter, sample containers (5), constant humidity salt for calibration (4 types), silica gel, grease
Options	Sample containers (10), constant humidity salt, sensor protection films (10), replacement packing, replacement sensor substrate



Please note that the product specifications are subject to change without prior notice.

 **Freund Corporation**

<http://www.freund.co.jp>



MIT TECHNOLOGY PTE. LTD.

31 Woodlands Close, #04-17 Woodlands Horizon, Singapore 737855

| E-mail: sale@mit-tec.com / calibration@mit-tec.com |

| Tel: 67423850 | Fax: 67423849 |

| www.mit-tec.com |

2016.09 (01.1000) 01. Printed in Japan

Your OTAL Solution