

Escort® ELF Sampling Pump

- Patented electronic laminar flow control.
- Internal secondary standard calibrates the pump continuously for compliance with OSHA 3058.
- Check against a primary standard only once a month or every 200 hours for coalmine dust sampling.
- Inlet filter traps moisture and particular matter.
- Stainless steel-filled plastic case provides EMI/RFI protection.
- Rated IP65 for resistance to water and dust ingress.
- Exceptionally quiet operation.
- Flow-Fault Indicator shows any sample inlet blockage.

- Run/Hold feature allows “time out” during sampling process.
- Elapsed time readout and low-battery warning.
- Low flow and dual tube sampling available with Gemini Twin-Port Sampler.

Approvals

Escort ELF Sampling Pumps are UL approved as intrinsically safe for use in hazardous locations – Class I, Groups A, B, C, D; Class II, Groups E, F, and G; and Class III, Division I locations. NIOSH certified for coal mine dust sampling (TC-74-030). MSHA certified as intrinsically safe for underground use (Approval No. 2G-3924-1). ATEX approved LOM 11ATEX2041 (select models). Pennsylvania DEP #BFE 6-11.



Competitive Advantages

- Patented “Laminar Flow” control permits the best accuracy in the business.
- Requires calibration only once per month or once every 200 hours for MSHA applications.
- “Key Pad” design allows adjustment of flow rates without tools or a potentiometer.
- Lightweight – only 23 ounces.
- Very durable design.
- Extremely easy to use.
- Resolution display is .1 LPM in standard mode, .01 LPM in calibration mode.
- 3 gaskets provide superior protection against water and dust ingress.
- Tamper-resistant door restricts access to adjustment keys.
- Designed for use with many different sampling accessories.

Escort ELF Specifications

- **Operating Flow Control**
Volumetric flow rate held within $\pm 2.5\%$ of set-point over the 1-to-3 LPM operating range ($\pm 5\%$ to 0.5 LPM), with automatic compensation for battery voltage, altitude, temperature and sample load changes.
- **Flow Rate**
Flow rate adjustable between 0.5 and 3 LPM; lower flow rates attainable (to 1 MLPM) with optional Gemini Twin-Port Sampling accessory.
- **Flow Indication**
Liquid Crystal Display provides 0.01 LPM resolution.
- **Operating Range**
30 inches of water load up to 2 LPM and 10 inches up to 3 LPM.
- **Flow Blockage Detection**
Flow-Fault LED comes on immediately when block is detected. Pump shuts down within 90 seconds if block is not cleared.
- **Elapsed Time Readout**
To 999 minutes in increments of 1 minute. Holds the last reading after either flow blockage or low battery shutdown and when pump is off or in hold mode.
- **Operating Time**
Varies with flow rate and sampling device loading.
- **Physical Weight**
23 oz. (652 gm), with battery pack.
- **Dimensions**
2.25" D x 4.25" H x 4" W (5.7 cm x 10.8 cm x 10.2 cm), with battery pack.
- **Power Supply**
4.8-volt battery pack of four nickel metal hydride cells.
- **Battery Pack Capacity**
2.8 amp hours
- **Battery Pack Recharge Time**
14-16 hours (overnight) with Omega™ Charger.
- **Typical Battery Pack Life**
300 or more charging cycles

Zefon
INTERNATIONAL

The Professionals Choice for Air Sampling Equipment

5350 SW 1st Lane, Ocala, FL 34474 USA | Tel: 352.854.8080 | Fax: 352.854.7480 | www.zefon.com

Escort® Pump Accessories



Calibration Devices

The calibration of a sampling pump is critical to the quality of samples taken. Calibration determines that the flow rate of air through the pump is accurate, within specified limits, usually $\pm 5\%$. A primary calibration device, the DigiCal™ Calibrator provides instantaneous calibration for instruments like the

Zefon Escort LCPump or the Escort ELF Sampling Pumps.

Just press the plunger and the DigiCal Calibrator does the work. Its unique flow cell replaces conventional bubble tubes and makes calibration easier. The DigiCal Calibrator achieves extreme accuracy by utilizing a computerized flow meter that provides instantaneous flow readouts on a digital display. Accurate measurements are possible within $\pm 0.5\%$ at any altitude.



Gemini® Twin-Port Sampler

For low-flow control when sorbent tubes are used, the patented Gemini Twin-Port Sampler is a valved mechanism that allows flow adjustment down to 1 MLPM (0.001 LPM to 600 MLPM total between both tubes). U.S. Patent No. 5,370,004. As an added benefit, the Gemini accessory permits

simultaneous sampling from sorbent tubes, with independently controlled flow rates of each. Dual sampling means two like sorbent tubes can be attached for simultaneous sampling at different flow rates, or two different tubes can be used to sample two types of substances at once.

Personal Pump Accessories



Leather Holster/Case with Belt Loop (# 811741)



36" Sampling Line with Tube Clip (#456226)



Metal Luer Adapter (#459743)



Universal Cassette or Cyclone Holder only (#ZA0061)



37mm, 2pcs, PVC, 50/Box (#725PVC)



10mm Static Conductive Nylon Cyclone (#ZA0081)



The Professionals Choice for Air Sampling Equipment

5350 SW 1st Lane, Ocala, FL 34474 USA | Tel: 352.854.8080 | Fax: 352.854.7480 | www.zefon.com